

Redtix NEW IMPACT WRENCH.



Applicable in the general industrial use, construction, MRO (Maintenance, Repair and Overhaul), rail, heavy machinery, oil and gas, shipbuilding, vehicle repair industry, heavy trucks, tire lanes and fleet maintenance.

New Composite Housing
Nylon with 40% fibre
Best hand feeling
High strength, non-deformable.

70% reduction.

Old Trigger
In high pressure state, it is not easy to trigger, you can't control the speed with your finger.



@90 PSI Force required to press the trigger 7.2 kgf

New Material
Magnesium alloy.

New Trigger
Great Control
Full teasing trigger.



Taiwan Patent M565632

@90 PSI Force required to press the trigger 2.1 kgf



New Motor
Industrial Motor
25% increase in performance.

New Regulator
More convenient to switch forward and reverse.



Best 45 degree angle air inlet
It also has the ability to rotate 360 degrees.
And can change six directions
Let the air hose position not affect your work.

* Tool 2m drop test **PASS.**

* Tool -24 degree Low temperature 1m drop test **PASS.**

Redtix NEW IMPACT WRENCH.



- * **Lightest** weight
- * **Largest** torque
- * **Fastest** tightening

Applicable in the general industrial use, construction, MRO (Maintenance, Repair and Overhaul), rail, heavy machinery, oil and gas, shipbuilding, vehicle repair industry, heavy trucks, tire lanes and fleet maintenance.

RT-19330-6

Anvil Extended 6"



Working Torque
1,763 Nm / 1,300 Ft-lb @ 5 Sec.
Loosening Torque
3,525 Nm / 2,600 Ft-lb @ 25 Sec.
Tool Weight
4.6 kg / 10.1 lbs



RT-19330

Working Torque
1,763 Nm / 1,300 Ft-lb @ 5 Sec.
Loosening Torque
3,525 Nm / 2,600 Ft-lb @ 25 Sec.
Tool Weight
3.7 kg / 8.14 lbs

